

SAFETY DATA SHEET
Asahi Solder Anode Ball
Sn95/Pb5
MSDS #: EAM2-2/41
Date of Preparation: September 2021

SECTION 1: CHEMICAL PRODUCT & COMPANY IDENTIFICATION

1.1 Product Details:

Product Name : Asahi Solder Anode Ball
Trade Name : Asahi Solder Anode Ball Sn95/Pb5
Use : Solder ball may be used in automated soldering for electronics and electrical assemblies.

1.2 Company's Identification:

Manufacturer's Name and Address : Singapore Asahi Chemical & Solder Industries Pte Ltd
47 Pandan Road
Singapore 609288
Telephone : (65) 6262-1616
Facsimile : (65) 6261-6311

1.3 Contact Point:

Designation : Chemist
Emergency Telephone Number: (65) 6262-1616

SECTION 2: HAZARD IDENTIFICATION

GHS classification

Acute toxicity
Oral : Category 4
Inhalation : Category 4
Carcinogenicity : Category 2
Reproductive Toxicity : Category 2
Specific target organ toxicity (repeated exposure) : Category 2 (nerves, kidney, reproductive system)
Acute aquatic toxicity : Category 1
Chronic aquatic toxicity : Category 1

GHS label elements



GHS Signal Word:	Warning
GHS Hazard Statement:	H302 Harmful if swallowed H332 Harmful if inhaled H351 Suspected of causing cancer H361 Suspected of damaging fertility or the unborn child H373 May cause damage to organs through prolonged or repeated exposure H410 Very toxic to aquatic life with long lasting effects
GHS Precautionary Statement:	
Prevention	
P201	Obtain special instructions before use.
P202	Do not handle until all safety precautions have been read and understood.
P260	Do not breathe dust, fume, gas, mist, vapours and spray.
P264	Wash hands thoroughly after handling.
P270	Do not eat or drink when using this product.
P271	Use only outdoors or in a well-ventilated area.
P273	Avoid releasing to the environment.
P281	Use personal protective equipment as required.
Response	
P308, P313, P314	IF exposed or concerned: Get medical advice or attention if you feel unwell.
P304, P340	IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing.
P301, P312, P330	IF SWALLOWED: Rinse mouth. Call a POISON CENTER or doctor/physician if you feel unwell.
P312	Call a POISON CENTER or doctor/physician if you feel unwell.
P391	Collect spillage.
Storage	
P405	Store locked up.
Disposal	
P501	Dispose of contents or container to appropriate waste site in accordance with local and national regulations.
Other Hazards	Inhalation or ingestion of lead dust or fumes may result in headache vomiting, abdominal spasms, fatigue, sleep disturbances, weight loss, anemia and leg, arm, and join pain.

SECTION 3: COMPOSITION/INFORMATION ON MATERIAL

Chemical Name	CAS No.	%	OSHA PEL(mg/m ³)	ACGIH TLY (mg/m ³)	Other Limits Recommended
Tin (Sn)	7440-31-5	95	2.0	2.0	
Lead (Pb)	7439-92-1	5	0.05	0.05	
Total		100			

SECTION 4: FIRST AID MEASURES

Ingestion : Seek medical attention.
Eye Contact : Flush eyes with plenty of water immediately for at 15 minutes. Seek medical attention.
Skin Contact : Wash thoroughly with soap and warm water.
Inhalation : Evacuate to a safe area with fresh air.

SECTION 5: FIRE-FIGHTING MEASURES

Extinguishing Media : NA
Fire Fighting Instructions : NA
Special Hazards : NA
Unusual Fire and Explosion Hazards : NA

SECTION 6: ACCIDENTAL RELEASE MEASURES

Leak/Spill : Place into properly labeled waste container and may be sent for recovery following appropriate recovery routes or methods.

SECTION 7: HANDLING AND STORAGE

Handling : Wash hand thoroughly with soap and water prior to eating, drinking or smoking. Do not smoke while soldering. Avoid inhalation of vapors and contact with skin and eyes. Observe good industrial practices.
Storage : Store in a cool environment away from oxidizing agents.

SECTION 8: EXPOSURE CONTROL AND PERSONAL PROTECTION

Engineering Measures : Maintain general or local exhaust ventilation to meet exposure limit requirements.
Personal Protection : Operator should be protected from soldering fumes
PROTECTIVE GLOVES : Impervious rubber
EYE PROTECTION : Safety glasses

SECTION 9: PHYSICAL AND CHEMICAL PROPERTIES

Appearance	: Metallic solid balls.
Odor	: No odor
Solubility in water:	: NA
Boiling Point(°C)	: 600°C
Liquidus(°C)	: 224°C
Solidus(°C)	: 183°C
Vapor Pressure(mm of Hg at 20°C)	: NA
Vapour Density (air=1)	: NA
Percentage Volatiles (by Volume)	: NA
Volatile Organic Compound (VOC)	: NA
Evaporation Rate (butyl acetate=1)	: NA
Specific Gravity (water=1 at 25°C)	: 7.42
Flash Point (°C)	: NA
Auto-ignition Temperature(°C)	: NE

SECTION 10: PHYSICAL HAZARDS (STABILITY AND REACTIVITY)

Condition to avoid	: Unknown.
Incompatibles	: Oxidizing materials.
Decomposition products	: Unknown.
Hazardous polymerization	: Will not occur.

SECTION 11: TOXICOLOGICAL INFORMATION

Toxicity data	: Lead is toxic and will cause damage to health if ingestion.
Carcinogenicity	: Not listed
Reproductive Effect	: Ingestion of lead will cause damage to the male reproductive system.
Effects of overexposure (Chronic Effect):	Breathing of vapors may produce respiratory irritation.
Target Organs	: Respiratory system and reproductive system
Medical Conditions Generally Aggravated by Exposure	: Soldering fumes may irritate the eyes.

SECTION 12: ECOLOGICAL INFORMATION

Mobility & Bioaccumulation	: Non volatile material
Biodegradability	: Non biodegradable
Aquatic Toxicity	: Lead is toxic and expected to be harmful to aquatic organisms

SECTION 13: DISPOSAL INFORMATION

Dispose according to federal, state and local regulations. This product is suitable for recovery following appropriate recovery routes or methods. If in doubt, contact Singapore Asahi.

SECTION 14: TRANSPORT INFORMATION
--

UN Number

ADR/RID:- IMDG:- IATA-DGR:-

UN proper shipping name

ADR/RID : Not dangerous goods

IMDG : Not dangerous goods

IATA-DGR : Not dangerous goods

Transport hazard class

ADR/RID:- IMDG:- IATA-DGR:-

Packaging group

ADR/RID:- IMDG:- IATA-DGR:-

Special shipping instruction

No data available

SECTION 15: REGULATORY INFORMATION

- a. Proposed classification : Harmful.
- b. Risk phrase
 - R20/21/22 Harmful by inhalation, in contact with skin and if swallowed.
 - R33 Danger of cumulative effect.
 - R36/37/38 Irritating to the eyes, respiratory system and skin.
 - R47 May cause birth defects.
 - R48 Danger of serious damage to health by prolonged exposure.
 - R52 Harmful to aquatic organisms.
- c. Safety phrase
 - S3/9/14 Keep in a cool, well ventilated place away from oxidizing agents.
 - S13 Keep away from food, drink and animal feeding stuff.
 - S23 Do not breathe fume or vapor.
 - S24/25/26/28 Avoid contact with skin or eyes. In case of contact with skin, rinse immediately with plenty of water. After contact with skin, wash immediately with plenty of water.
 - S35 This material with its container must be disposed of in a safe manner.
 - S36/37/39 Wear suitable protective clothing, gloves and eye/face protection.
 - S44 If you feel unwell, seek medical advice.
 - S46 If swallowed seek medical advice immediately.
 - S51 Use only in well ventilated areas.
 - S59 Refer to manufacturer/supplier for information on recovery/recycling.

SECTION 16: OTHER INFORMATION

THIS INFORMATION RELATES ONLY TO THE SPECIFIC MATERIAL DESIGNATED AND MAY NOT BE VALID FOR SUCH MATERIAL USED IN COMBINATION WITH ANY OTHER MATERIALS OR IN ANY PROCESS. SUCH INFORMATION IS TO THE

BEST OF THE COMPANY'S KNOWLEDGE AND BELIEVED ACCURATE AND RELIABLE AS OF THE DATE INDICATED. HOWEVER, NO REPRESENTATION, WARRANTY OR GUARANTEE IS MADE AS TO ITS ACCURACY, RELIABILITY OR COMPLETENESS. IT IS THE USER'S RESPONSIBILITY TO SATISFY HIMSELF AS TO THE SUITABILITY AND COMPLETENESS OF SUCH INFORMATION FOR HIS OWN PARTICULAR USE.

*optional

NE = Not Established

NA = Not Applicable

PEL = Permissible Exposure Level