

# SAFETY DATA SHEET Hasaconi QF2062

# Low Residue No Clean RMA Flux

SDS #: EFH 1-2/7

Date of Preparation: December 2023

# SECTION 1: CHEMICAL PRODUCT & COMPANY IDENTIFICATION

## 1.1 Product Details:

Product Name: Hasaconi Low Residue No Clean RMA Flux QF2062

Trade Name : Hasaconi QF2062

1.2 Company's Identification:

Manufacturer's Name and Address : Singapore Asahi Chemical & Solder

Industries Pte Ltd 47 Pandan Road Singapore 609288

Telephone : (65) 6262-1616 Facsimile : (65) 6261-6311

1.3 Contact Point:

Designation : Chemist

Emergency Telephone Number : (65) 6262-1616

# **SECTION 2: HAZARD IDENTIFICATION**

**GHS** classification

Flammable liquid : Category 2

Acute toxicity

Oral : Category 4
Dermal : Category 5
Inhalation : Category 5
Skin corrosion/irritation : Category 3
Serious eye damage/irritation : Category 2B

Specific target organ toxicity (single exposure) : Category 3 (Narcotic effects)

Aspiration hazard : Category 2

#### **GHS** label elements







GHS Signal Word: Danger

GHS Hazard Statement: H225 Highly flammable liquid and vapour

H302 Harmful if swallowed

H305 May be harmful if swallowed and enters airways

H313 May be harmful in contact with skin

H333 May be harmful if inhaledH316 Causes mild skin irritationH320 Causes eye irritation

H336 May cause drowsiness or dizziness

**GHS Precautionary Statement:** 

## Prevention

P210	Keep away from heat, sparks, open flames, hot surfaces.
P233	Keep container tightly closed.
P240	Ground/Bond container and receiving equipment.
P241	Use explosion-proof electrical and ventilating equipment.
P242	Use only non-sparking tools.
P243	Take precautionary measures against static discharge.
P261	Avoid breathing dust, fume, gas, mist, vapours and spray.
P264	Wash hands thoroughly after handling.
P270	Do not eat, drink or smoke when using this product.
P271	Use only outdoors or in a well-ventilated area.
P280	Wear protective gloves, eyes and face protections.

# Response

Response	
P301, P312, P330	IF SWALLOWED: Rinse mouth. Call a POISON CENTER or
	doctor/physician if you feel unwell.
P303, P361, P353	IF ON SKIN (or hair): Remove or take off immediately all
	contaminated clothing. Rinse skin with water or shower.
P304, P340	IF INHALED: Remove victim to fresh air and keep at rest in a
	position comfortable for breathing.
P305, P351, P338	IF IN EYES: Rinse cautiously with water for several minutes.
	Remove contact lenses, if present and easy to do. Continue
	rinsing.
P313, P332, P337	If eye or skin irritation persists: Get medical advice/attention.
P331	Do NOT induce vomiting.
P370, P378	In case of fire: Use foam, water spray or fog for extinction.

# Storage

P403, P233, P235 Store in a well-ventilated place. Keep container tightly closed and

cool.

Store locked up. P405

**Disposal** 

P501 Dispose of contents or container to appropriate waste site in

accordance with local and national regulations.

not result in Classification

**Other Hazards which do**: Repeated exposure may cause skin dryness or cracking. Slightly irritating to respiratory system. Vapours are heavier than air. Vapours may travel across the ground and reach remote ignition

sources causing a flashback fire danger.

# **SECTION 3: COMPOSITION/INFORMATION ON MATERIAL**

Chemical Name	CAS No.	%	OSHA PEL	ACGIH TLV	Other Limits
			(ppm)	(ppm)	Recommended
Aliphatic Alcohols	67-63-0	96.0	400	400	None Specified
Rosin	8050-09-07	2.40	-	-	-
Organic Acids	57-13-6	1.60	-	-	-
			-	-	-
Total		100			

## **SECTION 4: FIRST AID MEASURES**

## **Ingestion:**

Do not induce vomiting. If vomiting occurs spontaneously, keep head below hips to prevent aspiration. Transport to nearest medical facility for additional treatment.

#### **Eve Contact:**

Flush eyes with large amounts of water for at least 15 minutes. Get prompt medical attention.

#### **Skin Contact:**

Remove contaminated clothing. Flush with large amounts of water.

#### Inhalation:

Using respiratory protection, immediately remove victim from exposure. Administer CPR if breathing has stopped. Call for prompt medical attention.

# Most important symptoms/effects, acute and delayed:

Eye irritation signs and symptoms may include a burning sensation, redness, swelling, and/or blurred vision. Defatting dermatitis signs and symptoms may include a burning sensation and/or a dried/cracked appearance. Other signs and symptoms of central nervous system (CNS) depression may include headache, nausea, and lack of coordination. Respiratory irritation signs and symptoms may include a temporary burning sensation of the nose and throat, coughing, and/or difficulty breathing.

# Immediate medical attention, special treatment:

Causes central nervous system depression. Call a doctor or poison control center for guidance. Potential for chemical pneumonitis. Consider: gastric lavage with protected airway, administration of activated charcoal.

#### **SECTION 5: FIRE-FIGHTING MEASURES**

Clear fire area of all non-emergency personnel.

## **Suitable Extinguishing Media:**

Alochol-resistant foam, water spray or fog. Dry chemical powder, carbon dioxide, sand or earth may be used for small fires only. Do not discharge extinguishing waters into aquatic environment.

## Specific hazards arising from chemicals:

Flammable liquid, can release vapors that form flammable mixtures at temperatures at or above the flashpoint. Try to cover liquid spills with foam.

## **Protective Equipment & Precautions for Fire Fighters:**

Wear full protective clothing and self-contained breathing apparatus.

## **SECTION 6: ACCIDENTAL RELEASE MEASURES**

Observe all relevant local and international regulations.

# Personal Precautions, Protective Equipment and Emergency Procedures:

Avoid contact with spilled or released material. Immediately remove all contaminated clothing. For guidance on selection of personal protective equipment see SECTION 8.

#### **Environmental Precautions:**

Shut off leaks, if possible without personal risks. Remove all possible sources of ignition in the surrounding area. Use appropriate containment (of product and fire fighting water) to avoid environment contamination. Prevent from spreading or entering drains, ditches or rivers by using sand, earth, or other appropriate barriers. Attempt to disperse the vapour or to direct its flow tot a safe location for example by using fog sprays. Take precautionary measures against static discharge. Ensure electrical continuity by bonding and grounding (earthing) all equipment. Monitor area with combustible gas indicator.

#### Methods and Materials for Containment and Clean Up:

Transfer spilled liquid by mechanical means to a labelled, sealable container for product recovery or safe disposal. Allow residues to evaporate or soak up with an appropriate absorbent material and dispose safely. Remove contaminated soil and dispose safely.

## **SECTION 7: HANDLING AND STORAGE**

#### **General Precautions:**

Avoid breathing vapours or contact with material. Only use in well ventilated areas. Wash thoroughly after handling.

## **Precautions for Safe Handling:**

Electrostatic charges may be generated during pumping. Electrostatic discharge may cause fire. Ensure electrical continuity by bonding and grounding (earthing) all equipment. Restrict line velocity during pumping in order to avoid generation of electrostatic discharge (<= 10 m/sec). Avoid splash filling. Do NOT use compressed air for filling, discharging, or handling operations. Extinguish any naked flames. Do not smoke. Remove ignition sources. Avoid sparks. Handling Temperature: Ambient.

## **Conditions for Safe Storage:**

Keep away from aerosols, flammables, oxidizing agents, corrosives and from products harmful or toxic to human or to the environment. Must be stored in a well-ventilated area, away from sunlight, ignition sources and other sources of heat. Storage Temperature: Ambient.

# SECTION 8: EXPOSURE CONTROL AND PERSONAL PROTECTION

Engineering Measures : Maintain general or local exhaust ventilation to meet

exposure limit requirements.

Respiratory Protection : NIOSH/MSHA approved respirators may be necessary to

prevent overexposure by inhalation.

Protective Gloves : Chemical resistant gloves.

Eye Protection : Wear safety glasses with side shields.

Other Protective Equipment : For open systems where contact is likely, wear long sleeves,

chemical resistant gloves and chemical goggles.

Work Hygienic Practices : Do not eat, drink, or smoke in work area.

## **SECTION 9: PHYSICAL AND CHEMICAL PROPERTIES**

Appearance : Clear transparent colorless liquid

Odor : Alcohol odor Solubility in water: : Slightly soluble

Boiling Point(°C) : 78°C

Melting Point(°C) : NE

Vapor Pressure(mm of Hg at 20°C) : NE

Vapor Density (air=1) : NA

Percentage Volatiles (by Volume) : NE

Volatile Organic Compound (VOC) : ~89%

Evaporation Rate (butyl acetate=1) : NE

Specific Gravity (water=1 at 25°C) :  $0.805 \pm 0.005$  @ 25°C

Flash Point (°C) : 11.7°C by TCC

Lower Explosive Limit : NE Upper Explosive Limit : 2.5 Auto-ignition Temperature(°C) : 455.6°C

# SECTION 10: PHYSICAL HAZARDS (STABILITY AND REACTIVITY)

Chemical Stability : Stable under normal temperature and pressure.

Possibility of Hazardous : Data not available

Reaction

Condition to avoid : Direct contact with flame and excessive heating

Incompatible materials : strong oxidizing agents. Strong acids.

Hazardous Decomposition

products

: None specified.

Hazardous polymerization : Will not occur.

# **SECTION 11: TOXICOLOGICAL INFORMATION**

Toxicity data : None.
Carcinogenicity : Not listed.
Reproductive Effect : None.

Germ Cell Mutagenicity : Not mutagenic.

Inhalation Toxicity : May cause headache and dizziness, are anesthetic and may have

other central nervous system effects.

Acute Ingestion : Small amounts of the liquid aspirated into the respiratory

systems during ingestion, or from vomiting may cause

bronchiopneumonia or pulmonary edema.

Serious Eye : Irritating to eyes.

Damage/Irritation

Respiratory or Skin : Not a skin sensitizer.

Sensitisation

Aspiration Hazard : Aspiration into the lungs when swallowed or vomited may

cause chemical pneumonitis which can be fatal.

Medical Conditions Generally Aggravated

by Exposure

: None specified.

# **SECTION 12: ECOLOGICAL INFORMATION**

Mobility & Bioaccumulation : Volatile material. Biodegradability : Non biodegradable.

Aquatic Toxicity : NE

# **SECTION 13: DISPOSAL INFORMATION**

Material Disposal : It is the responsibility of the waste generator to determine the toxicity

and physical properties of the material generated to determine the proper waste classification and disposal methods in compliance with applicable regulations. Do not dispose into the environment in drains or in water courses. Waste product should not be allowed to contaminate

soil or water.

Container Disposal : Drain container thoroughly. After draining, vent in a safe place away

from sparks and fire. Residues may cause an explosion hazard. Do not puncture, cut, or weld uncleaned drums. Send to drum recoverer or

metal reclaimer.

Local Legislation : Disposal should be in accordance with applicable regional, national, and

local laws and regulations. Local regulations may be more stringent than

Page **6** of **8** EFH 1-2/7

## **SECTION 14: TRANSPORT INFORMATION**

**UN Number** 

ADR/RID: 1993 IMDG: 1993 IATA-DGR: 1993

**UN Proper Shipping Name** 

ADR/RID : Flammable Liquid n.o.s. (Isopropyl Alcohol)
IMDG : Flammable Liquid n.o.s. (Isopropyl Alcohol)
IATA/DGR : Flammable Liquid n.o.s. (Isopropyl Alcohol)

**Transport Hazard Class** 

ADR/RID: 3 IMDG: 3 IATA-DGR: 3

**Packaging Group** 

ADR/RID: II IMDG: II IATA-DGR: II

**Environmental Hazards** 

ADR/RID: no IMDG Marine pollutant: no IATA-DGR: no

# **Special shipping instruction**

No data available

## **SECTION 15: REGULATORY INFORMATION**

a. Proposed classification : Harmful.

b. Risk phrase

R11 Highly flammable.

R20/21/22 Harmful by inhalation, in contact with skin and if swallowed

R36/37/38 Irritating to the eyes, respiratory system and skin.

c. Safety phrase

S3/7/9 Keep container tightly closed, in a cool well ventilated place.

S20/21 When using, do not eat, drink or smoke.

S23 Do not breathe fume or vapor.

S24/25/26 Avoid contact with skin or eyes. In case of contact with skin,

rinse immediately with plenty of water.

S36/37/39 Wear suitable protective clothing, gloves and eye/face protection.
S47/49 Keep only in the original container at temperature not exceeding 25°C.

Refer to manufacturer/supplier for information on recovery/recycling.

## **SECTION 16: OTHER INFORMATION**

THIS INFORMATION RELATES ONLY TO THE SPECIFIC MATERIAL DESIGNATED AND MAY NOT BE VALID FOR SUCH MATERIAL USED IN COMBINATION WITH ANY OTHER MATERIALS OR IN ANY PROCESS. SUCH INFORMATION IS TO THE

BEST OF THE COMPANY'S KNOWLEDGE AND BELIEVED ACCURATE AND RELIABLE AS OF THE DATE INDICATED.

HOWEVER, NO REPRESENTATION, WARRANTY OR GUARANTEE IS MADE AS TO ITS ACCURACY, RELIABILITY OR COMPLETENESS. IT IS THE USER'S RESPONSIBILITY TO SATISFY HIMSELF AS TO THE SUITABILITY AND COMPLETENESS OF SUCH INFORMATION FOR HIS OWN PARTICULAR USE.

# \*optional

NE = Not Established NA = Not Applicable PEL = Permissible Exposure Level