



**SAFETY DATA SHEET**  
**Asahi Solder Paste**  
**No-Clean M097 Series**  
*Sn62.8 / Pb36.8 / Ag0.4*  
*SDS #: EAP2-32/20*  
*Date of Preparation: February 2024*

**SECTION 1: CHEMICAL PRODUCT & COMPANY IDENTIFICATION**

**1.1 Product Details:**

Product Name : Asahi No-Clean Solder Paste  
Trade Name : SnPbAg0.4 4-5M097  
Use : Solder paste may be used in automated soldering for electrical or electronic assemblies.

**1.2 Company's Identification:**

Manufacturer's Name and Address : Singapore Asahi Chemical & Solder Industries Pte Ltd  
47 Pandan Road  
Singapore 609288

Telephone : (65) 6262-1616  
Facsimile : (65) 6261-6311

**1.3 Contact Point:**

Designation : Chemist  
Emergency Telephone Number : (65) 6262-1616

**SECTION 2: HAZARD IDENTIFICATION**

**GHS classification**

Acute toxicity  
Oral : Category 4  
Inhalation : Category 4  
Dermal : Category 5

Sensitization  
Skin : Category 1  
Respiratory : Category 1

Skin Corrosion/Irritation : Category 3  
Serious Eye Damage/Irritation : Category 2B  
Carcinogenicity : Category 2  
Reproductive Toxicity : Category 2

Specific target organ toxicity (repeated exposure) : Category 2 (nerves, kidney, reproductive system)  
 Acute aquatic toxicity : Category 1  
 Chronic aquatic toxicity : Category 1

**GHS label elements**



**GHS Signal Word:** Danger

**GHS Hazard Statement:**

- H302 Harmful if swallowed
- H332 Harmful if inhaled
- H313 May be harmful in contact with skin
- H316 Causes mild skin irritation
- H320 Causes eye irritation
- H317 May cause an allergic skin reaction
- H334 May cause allergy or asthma symptoms or breathing difficulties if inhaled
- H351 Suspected of causing cancer
- H361 Suspected of damaging fertility or the unborn child
- H373 May cause damage to organs through prolonged or repeated exposure
- H410 Very toxic to aquatic life with long lasting effects

**GHS Precautionary Statement:**

**Prevention**

P201 Obtain special instructions before use.  
 P202 Do not handle until all safety precautions have been read and understood.  
 P260 Do not breathe dust, fume, gas, mist, vapours and spray.  
 P264 Wash hands thoroughly after handling.  
 P270 Do not eat or drink when using this product.  
 P271 Use only outdoors or in a well-ventilated area.  
 P272 Contaminated work clothing should not be allowed out of the workplace.  
 P273 Avoid releasing to the environment.  
 P281 Use personal protective equipment as required.  
 P285 In case of inadequate ventilation wear respiratory protection.

**Response**

P302, P352 IF ON SKIN: Wash with plenty of soap and water.  
 P305, P351, P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.  
 P308, P313, P314 IF exposed or concerned: Get medical advice or attention if you feel unwell.  
 P332, P337, P313 If eye or skin irritation occurs Get medical advice/attention.

P333, P 313                    If skin irritation or rash occurs: Get medical advice/attention.  
P304, P340                    IF INHALED: Remove victim to fresh air and keep at rest in a  
   position comfortable for breathing.  
P301, P312, P330            IF SWALLOWED: Rinse mouth. Call a POISON CENTER or  
   doctor/physician if you feel unwell.  
P312                                Call a POISON CENTER or doctor/physician if you feel unwell.  
P391                                Collect spillage.

**Storage**  
P405                                Store locked up.

**Disposal**  
P501                                Dispose of contents or container to appropriate waste site in  
accordance with local and national regulations.

**Other Hazards which do not result in Classification** : Inhalation or ingestion of lead dust or fumes may result in headache vomiting, abdominal spasms, fatigue, sleep disturbances, weight loss, anemia and leg, arm, and join pain. Inhalation of fumes during solder operation may cause stimulation of throat and nose feeling sick.

**SECTION 3: COMPOSITION/INFORMATION ON MATERIAL**

Chemical Name	CAS No.	%	OSHA PEL(mg/m <sup>3</sup> )	ACGIH TLY (mg/m <sup>3</sup> )	Other Limits Recommended
Tin (Sn)	7440-31-5	50.9-63.7	2.0	2.0	-
Lead (Pb)	7439-92-1	30.6-36.0	0.05	0.05	-
Silver (Ag)	7440-22-4	0.3-0.4	0.01(powder/dust)	0.01(powder/dust)	
Rosin	8050-09-07	3.4-6.9	NE	NE	-
Organic Thixotropic Mixture	Proprietary	1.0-3.8	NE	NE	
Hydrocarbon	Proprietary	1.0-3.8	NE	NE	
<b>Total</b>		<b>100</b>			

**SECTION 4: FIRST AID MEASURES**

**Ingestion:**  
If victim is conscious and can swallow, dilute stomach contents with 2-4 cups of water or milk. Do not induce vomiting. Seek medical attention and never give anything by mouth to an unconscious person.

**Eye Contact:**  
Flush eyes with plenty of water immediately for at 15 minutes. Seek medical attention.

**Skin Contact:**  
Wash thoroughly with soap and warm water. Seek medical attention if irritation develops or persists.

**Inhalation:**

Remove victim from exposure area to fresh air immediately. If breathing has stopped, give artificial respiration. Keep affected person warm and at rest medical oxygen may be administered, if available, where breathing is difficult. Seek immediate medical attention.

**Most important symptoms/effects, acute and delayed:**

Headache, nausea, vomiting, abdominal spasms, fatigue, sleep disturbances, weight loss, anemia and leg, arm, and joint pain.

**Immediate medical attention, special treatment:**

Call a doctor or poison control center for guidance.

**SECTION 5: FIRE-FIGHTING MEASURES****Suitable fire-extinguishing media:**

Use any means of extinction appropriate for surrounding fire conditions such as water spray, carbon dioxide, dry chemical, or foam.

**Fire and explosion hazards :**

Massive metal is not flammable or combustible, Finely divided lead dust or powder is a moderate fire hazard and moderate fire hazard and moderate explosion hazard when dispersed in the air at high concentrations and exposed to heat, flame, or incandescents. Explosions may also occur upon contact with certain incompatible materials.

**Specific hazards arising from the chemical:**

Highly toxic lead oxide fumes may evolve in fires.

**Fire Fighting Instructions:**

If possible, move material from fire area and cool material exposed to flame. Highly toxic lead oxide fumes may evolve in fires. Fire fighters must be fully trained and wear full protective clothing including an approved, self-contained breathing apparatus which supplies a positive air pressure within a full face-piece mask.

**SECTION 6: ACCIDENTAL RELEASE MEASURES****Procedures for Cleanup:**

Control source of spillage if possible to do so safely. Clean up spilled material immediately, observing precautions in Section 8, Personal Protection. Molten metal should be allowed to solidify before cleanup. If solid metal, wear gloves, pick up and return to process. If dust, wear recommended personal protective equipment and use methods which will minimize dust generation. Place contaminated material in suitable labelled containers for recovery or disposal.

**Environment Precautions:**

Lead metal has limited bioavailability but its compounds can pose a severe threat to the aquatic and terrestrial environments. Contamination of water and soil should be prevented.

## SECTION 7: HANDLING AND STORAGE

### Precautions for safe handling:

Wash hand thoroughly with soap and water prior to eating, drinking or smoking. Do not smoke while soldering. Avoid inhalation of vapors and contact with skin and eyes. Observe good industrial practices.

### Conditions for safe storage, including any incompatibilities:

Store in a dry, covered area away from incompatible materials, strong acids and food or feedstuffs. Solid metal suspected of containing moisture should be THOROUGHLY DRIED before being added to a molten bath. Otherwise, entrained moisture could expand explosively and spatter molten metal out of the bath.

## SECTION 8: EXPOSURE CONTROL AND PERSONAL PROTECTION

### Engineering Measures:

Use adequate local or general ventilation to maintain the concentration of lead fumes in the working environment well below recommended occupational exposure limits. Supply sufficient replacement air to make up for air removed by the exhausted system. Local exhaust is recommended for melting, casting, grinding, burning, and use of powders.

### Personal Protection:

Gloves and coveralls or other work clothing are recommended to prevent prolonged or repeated direct skin contact when lead is processed. Appropriate eye protection should be worn where fume or dust is generated. Where hot or molten metal is handled, heat resistant gloves, goggles or face shield, and clothing to protect from hot metal splash should be worn. Safety type boots are recommended.

### Respirators:

Where lead dust or fumes are generated and cannot be controlled to within acceptable levels by engineering means, use appropriate NIOSH-approved respiratory protection equipment (a 42CFR84 Class N, R or P-100 particulate filter cartridge). When exposure levels are unknown, a self-contained breathing apparatus which supplies a positive air pressure within a full face-piece mask should be worn.

## SECTION 9: PHYSICAL AND CHEMICAL PROPERTIES

Appearance	: Grayish cream
Odor	: Mild Solvent Odor
Solubility in water:	: Negligible by weight
Boiling Point(°C)	: Flux – 124°C; Alloy – 600°C
Melting Point(°C)	: Alloy - 179 to183°C
Vapor Pressure(mm of Hg at 20°C)	: NA
Vapour Density (air=1)	: NA
Viscosity	: 1000 ± 15% kcPs
Percentage Volatiles (by Volume)	: NA
Volatile Organic Compound (VOC)	: 5.2% by weight
Evaporation Rate (butyl acetate=1)	: NA
Specific Gravity (water=1 at 25°C)	: NA

Flash Point (°C) : 238°C (COC)  
Auto-ignition Temperature(°C) : NE

## SECTION 10: PHYSICAL HAZARDS (STABILITY AND REACTIVITY)

### **Chemical Stability:**

Massive metal is stable under normal temperatures and pressures.

### **Possibility of Hazardous Reaction:**

Data not available

### **Condition to avoid:**

Contact with incompatible materials.

### **Incompatible Materials:**

Lead reacts vigorously with strong oxidizers, such as hydrogen peroxide and chlorine trifluoride, and active metals, such as sodium and potassium. Powdered lead metal in contact with disodium acetylide, chlorine trifluoride sodium carbide or fused ammonium nitrate poses a risk of explosion. Solution of sodium azide in contact with lead metal can form lead azide, which is a detonating compound. A lead-zirconium alloy (10-70% Zr) will ignite when struck with a hammer.

### **Hazardous Decomposition Products:**

High temperature operations will generate highly toxic lead oxide fume. Lead oxide is highly soluble in body fluids and the particle size of the metal fumes is largely within the respirable size range, which increases the likelihood of inhalation and deposition of the fume within the body.

## SECTION 11: TOXICOLOGICAL INFORMATION

### **General:**

Lead accumulates in bone and body organs once it enters the body. Elimination from the body is slow. Initial and periodic medical examinations are advised for persons repeatedly exposed to levels above the exposure limits of lead dust or fumes. Once lead enters the body, it can affect a variety of organ systems, including the nervous system, kidneys, reproductive system, blood formation, and gastrointestinal system. The primary routes of exposure to lead are inhalation or ingestion of dust and fumes.

### **Acute:**

- Skin/Eye** : Contact with dust or fume may cause local irritation but would not cause tissue damage.
- Inhalation** : Exposure to lead dust or fume may cause headache, nausea, vomiting, abdominal spasms, fatigue, sleep disturbances, weight loss, anemia, and pain in legs, arms, and joints. An acute, short-term dose of lead could cause acute encephalopathy with seizures, coma, and death. However, short-term exposure of this magnitude is rare. Kidney damage, as well as anemia, can occur from acute exposure.
- Ingestion** : Symptoms due to ingestion of lead dust or fume would be similar to those from inhalation. Other health effects such as metallic taste in the mouth and constipation or bloody diarrhea might also be expected to occur.

**Reproductive Effect :**

Ingestion of lead will cause damage to the male reproductive system.

**Effects of overexposure (Chronic Effect):**

Breathing of vapors may produce respiratory irritation.

**Long term (chronic) overexposure:**

Prolonged exposure to lead dust and fume may produce many of the symptoms of short-term exposure and may also cause central nervous system damage, gastrointestinal disturbances, anemia, and, rarely, wrist drop. Reduced hemoglobin production has been associated with low lead exposures. Symptoms of central nervous system damage due to moderate lead exposure include fatigue, headaches, tremors and hypertension. Very high lead exposure can result in lead encephalopathy with symptoms of hallucinations, convulsions, and delirium. Kidney dysfunction and possible injury has also been associated with chronic lead poisoning. Chronic over-exposure to lead has been implicated as a causative agency for the impairment of male and female reproductive capacity. Pregnant women should be protected from excessive exposure as lead can cross the placental barrier and unborn children may suffer neurological damage or developmental problems due to excessive lead exposure in pregnant women.

<b>SECTION 12: ECOLOGICAL INFORMATION</b>
---

Mobility & Bioaccumulation : Non volatile material

Biodegradability : Non biodegradable

Aquatic Toxicity : Lead is toxic and expected to be harmful to aquatic organisms

<b>SECTION 13: DISPOSAL INFORMATION</b>
---

Dispose according to federal, state and local regulations. This product is suitable for recovery following appropriate recovery routes or methods. If in doubt, contact Singapore Asahi.

<b>SECTION 14: TRANSPORT INFORMATION</b>
--

**UN Number**

ADR/RID:-

IMDG:-

IATA-DGR:-

**UN proper shipping name**

ADR/RID : Not dangerous goods

IMDG : Not dangerous goods

IATA-DGR : Not dangerous goods

**Transport hazard class**

ADR/RID:-

IMDG:-

IATA-DGR:-

**Packaging group**

ADR/RID:-

IMDG:-

IATA-DGR:-

**Special shipping instruction**

No data available

**SECTION 15: REGULATORY INFORMATION**

Safety, health and environmental regulations/legislation specific for the substance or mixture  
EU Regulation (EC) No. 1907/2006 (REACH)

**Substances of very high concern**

None of the components are listed.

**UNECE Aarhus Protocol on POPs and Heavy Metals**

Not listed.

**SECTION 16: OTHER INFORMATION**

THIS INFORMATION RELATES ONLY TO THE SPECIFIC MATERIAL DESIGNATED AND MAY NOT BE VALID FOR SUCH MATERIAL USED IN COMBINATION WITH ANY OTHER MATERIALS OR IN ANY PROCESS. SUCH INFORMATION IS TO THE BEST OF THE COMPANY'S KNOWLEDGE AND BELIEVED ACCURATE AND RELIABLE AS OF THE DATE INDICATED.

HOWEVER, NO REPRESENTATION, WARRANTY OR GUARANTEE IS MADE AS TO ITS ACCURACY, RELIABILITY OR COMPLETENESS. IT IS THE USER'S RESPONSIBILITY TO SATISFY HIMSELF AS TO THE SUITABILITY AND COMPLETENESS OF SUCH INFORMATION FOR HIS OWN PARTICULAR USE.

\*optional

NE = Not Established

NA = Not Applicable

PEL = Permissible Exposure Level